

X-PER Vertical Air Partition VQ-9 series



VQ-9



Features

- 22-24 m/s airflow velocity
- Up to 18000 CMH airflow volume
- Totally Enclosed Motor IP44
- Air Curtain Unit IPX4
- Thermally protected motors
- Custom-made to door height
- Strong and self-supporting
- Complete with Filter Panels
- EG Steel (Powder-coated)
- SUS304/316L versions available

**THE PERFECT BARRIER FOR
BLOCKING HEAT, DUST, AND INSECTS**



X-Per Technia (Thailand) Co., Ltd.

29/33-35 Moo 11, Boromrachachonnani Rd., Salathammasop, Taweewattana, Bangkok 10170. Thailand.

Tel: +66-2-888-2995 to 8 Fax: +66-2-888-2994 email: inquiry@xperasia.com

 **X-PER**
Air Curtain



X-Per VQ-9 series of vertical Air Partition are designed specially for insect blocking application in industrial environment. Capable of delivering a maximum airflow velocity of 24 m/s and a maximum airflow volume of 18,000 CMH.

With X-Per's new modular nozzle design, the high speed airflow is spread out across the door, forming an invisible wall for blocking insects and dust.

Available with unfiltered and filtered air intake grills. Standard construction is powder-coated Electro-galvanized steel. Also available in stainless steel 304 and 316L.



Dimension & Performance

Model	Dimension (mm)			Max Airflow Velocity		Max Airflow Volume	
	Width	Depth	Height	FPM	m/s	CFM	CMH
VQ-9E	600	650	Custom	4400-4800	22-24	< 10594	< 18000

Specifications

Model	Voltage	Freq	Phase	Current	Power	Weight	
	V	Hz	Φ	Ampere	Watt	Kg	lb
VQ-9E	380	50	3	< 11	< 2400	< 400	< 882

Note: Model name with suffix "E" denotes filtered air intake grills.
Airflow Volume, Current, Power, and Weight are subject to change according to unit height.