

X-PER Air Curtain XP-6R / XP-6SR Commercial Series



XP-6R XP-6SR



Features

- 12 m/s air flow velocity
- Over 2,840 CMH
- 90 and 120 cm in length
- Cross-flow impellers
- Totally enclosed motor
- Direct Drive
- Self-lubricating ball bearing
- Motor rated at IP22
- Galvanized Steel construction
- Powder Coating finish
- Manual/Automatic modes
- Low operating costs
- Easy maintenance
- Horizontal mounting
- Long life time
- Quick and easy to install
- Environmental friendly
- High quality

THE PERFECT BARRIER FOR BLOCKING HEAT, INSECTS, AND DUST



X-Per Technia (Thailand) Co., Ltd.

29/33-35 Moo 11, Boromrachachonnani Rd., Salathammassop, Taweewattana, Bangkok 10170. Thailand.

Tel: +66-2-888-2995 to 8 Fax: +66-2-888-2994 email: inquiry@xperasia.com





The XP-6R series of commercial air curtains are made from galvanized steel with powder coating finish.

The impellers are directly driven. The motors used are of totally enclosed type with self-lubricating ball bearings. The motor has a protection rating of IP22.

With appropriate controller, the XP-6R can be configured to operate in manual as well as automatic modes whereby the air curtain units will operate only when the door is opened.

Dimension & Performance

Type	Model	Dimension (mm)			Airflow Velocity		Airflow Volume	
		Length	Height	Thickness	FPM	m/s	CFM	CMH
Horizontal Mount	XP-609R	900	262	252	2200	11	1109	1883
	XP-612R	1200					1535	2607
	XP-609SR	900			2400	12	1209	2054
	XP-612SR	1200					1674	2843

Specifications

Type	Model	Voltage	Freq	Phase	Current	Power	Weight	
		V	Hz	Φ	A	W	kg	lb
Horizontal Mount	XP-609R	220-240	50	1	1.08	230	20.7	45.6
	XP-612R				1.39	305	24.2	53.4
	XP-609SR				1.21	254	20.9	46.1
	XP-612SR				1.51	336	24.4	53.8